Layman defibrillation to help sudden cardiac arrest



Quickly applied ME PAD saves lifes

ME PAD and ME PAD Automatic are a layman defibrillator to help during sudden cardiac arrest.

Sudden cardiac death is a direct result of cardiac arrhythmias with approximately 150,000 cases per year in Germany alone, now one of the leading causes of death. The unexpected cardiac and circulatory arrest leads after one to two minutes to unconsciousness. Without help it decreases the chance of survival of the patient, by about 10-12 % with each additional minute.

If there is a risk of a sudden cardiac death, the only saving measure is the so-called early defibrillation. ME PAD & ME PAD Automatic have been specifically developed for use by laymen. Clear voice instructions and pictograms guide the helper through the entire resuscitation. Thus, without prior medical training, professional help can be immediately provided.

Features and Benefits

- Specially developed for use by laymen
- Available fully automatic speak various languages
- Internally save all relevant data of the last 5 resuscitations
- Strong Lithium-ion battery: stand-by for up to 5 years or 200 shocks
- Automatic volume adjustment to sound level of the surrounding environment
- Determine the impedance of the patient and evaluate the ECG of the patient
- CPR guide indicator
- Displaying Life expectancy of Electrode
- Automatic daily, weekly and monthly self-test
- Fullfuill military standard MIL-STD 810G and IP55
- Emergency change to pediatric without changing pads
- Waveform: E-cube two phases
- Internal monitoring of the electrode pads for quality
- Always up-to-date through software updates
- Supplied complete with battery, electrode pads for adults and carrying bag
- 5 years full warranty

Layman defibrillation to help sudden cardiac arrest

How To Use ME PAD Defibrillators


ME PAD defibrillators are ready to use at any place. Up to five operations of three hours of duration can be recorded on the internal SD memory card. At any time, all the important data such as heart rhythm, energy output, time, etc. are available for post-analysis. Software developed in compliance with current ERC guidelines. Detailed instructions are given to the user through the entire CPR.

1. Preperation and Power button



- Set the Adult / Pediatric selection switch to match the victim.
- Turn the device on by pressing the Power button.

2. Attaching pads



- Remove clothes from patient's chest.
- Remove the pads package from the pads storage compartment at the bottom of the device.
- Remove the pad cover and place pads on the patient.

3. Shock delivery after analyzing heart rhythm



- Keep away from the patien during analyzing heart rhythm.
- Press the Shock button if instructed.

*Please check the user manual for detailed instructions

The Main Function of ME PAD Defibrillators

- Comprehensible voice instructions and pictograms guide the helper through the resuscitation.
- Emergency switchover to children under 25 kg possible without changing the electrode.
- All relevant data of the last 5 resuscitations are stored.
- Automatic self-test and indication of readiness on the display.
- Automatic adjustment of the volume of the voice announcements to the environment.



Layman defibrillation to help sudden cardiac arrest

Specifications

Dimension Size: 260 (W) x 256 (L) x 69.5(H) mm Weight: 2.4 kg including battery & pads

Defibrillation

Adult: 150 J at 50 Ω Output energy:

Pediatric: 50 J at 50 Ω (common usage)

Charging time:

Charging time after

CPR finished:

at least 8 seconds

E-cube two-phase (truncated expotential type) Waveform:

less than 8seconds

ECG

Lead II Acquired ECG lead: 1 Hz to 30 Hz Frequency: 25 Ω to 175 Ω Impendance range:

(Schock will not be delivered if the patient's

impedance is beyond this range)

Shockable Rhythms: Ventricular Fibrillation or Fast Ventricular

Fibrillation

Sensitivity and Specificity: meets ANSI/AAMI DF80 guidelines

Operational Guidance

Status LCD:

Control Devices: Power Button, i-Button, Shock Button (only ME

> PAD semi), Adult/Pediatric Selection Switch Displays device status, battery level and pads

Plays back voice instructions. The CU-SP1 Speaker:

analyzes the ambient noise level during a treatment operation. If ambient noise level is high, it automatically increases the voice instructions volume so that you can hear them

clearly.

Self-Diagnostic Test

Auto: Power On Self-Test, Run-time Self-Test

Daily, Weekly, and Monthly Self-Test

Manuel: Battery Pack Insertion Test (done when the user

inserts the battery pack into the battery pack

compartment of the device)

Disposable Battery Pack

12V DC, 4.2Ah LiMnO2 Battery type:

Disposable: Long-life

Capacity: At least 200 shocks for a new battery or 8 hours

of operating time at room temperature

Standby Life At least 5 years from the date of manufacture if

(After inserting battery): stored and maintained in accordance with the

instructions in this document.

Operating: 0 °C to 43 °C Temperature ranges:

Storage: -20 °C to 60 ° C

Pads

• Adult Defibrillation Pads

 120 cm^2 Electrode area:

120 cm (Inside the pouch: 95 cm, Cable length:

Outside the pouch: 25 cm)

Shelf life: Up to 30 months from the date of manufacture

Pediatric Defibrillation Pads

Electrode area: 46.43 cm²

Total 120 cm (Inside the pouch: 80 cm, Cable length:

Outside the pouch: 40 cm)

Shelf life: Up to 24 months from the date of manufacture

Data Storage and Transfer

Internal memory data 5 individual treatments, up to 3 hours per

capacity:

treatment

SD card: External memory. Data may be copied from

the internal memory to the SD Card

IrDA: For PC communications

Standards

meets DIN EN 60529: IP55 Sealing:

ESD: meets EN 61000-4-2:2001

EMI (Radiated): meets EN 60601-1-2 limits, method

EN 55011:2007 + A2:2007, Group 1, Class B EMI (Immunity): meets IEC 60601-1-2 limits, method

EN 61000-4-3:2006 +A1:2008 Level 3

(10V/m 80MHz to 2500MHz)

Vibration: Operating: Meets MIL-STD-810G Fig.514.6E-1,

random

Standby: Meets MIL-STD-810G Fig.514.6E-2,

swept sine (helicopter)

Languages: German, English, French, Danish, Spanish,

Norwegian, Italian, Czech, Portuguese, Greek,

Swedish, Dutch, Polish, Lithuanian

Environment Conditions

Altitude: 0 to 15,000 feet (operational and storage)

Drop: withstands 1.2-meter drop to any edge, corner,

or surface

Temperature range: Operation: 0° C to 43° C

Standby: 0° C to 43° C Transport: -20° C to 60° C

Humidity range: Operation: 5% ~ 95% (non condensing)

Standby: 5% ~ 95% (non condensing) Transport: 5% ~ 95% (non condensing)

Accessory

 Standard Battery

Pads Bag

Wall holder Optional

Wall cabinet Pediatric pads

Layman defibrillation to help sudden cardiac arrest

Specifications

Scenario (ME PAD Trainer)

Scenario 1 (S1): 1. Apply first shock, CPR

2. Reproduce normal rhythm, CPR

Scenario 2 (S2): 1. Apply first shock, CPR

2. Apply second shock, CPR

3. Reproduce normal rhythm, CPR

Scenario 3 (S3): 1. Reproduce normal rhythm, CPR

2. Apply first shock, CPR

3. Reproduce normal rhythm, CPR

Scenario 4 (S4): 1. Reproduce normal rhythm continuosly, CPR

Scenario 5 (S5): 1. Apply first shock, CPR

Reproduce normal rhythm, CPR
 Apply second shock, CPR
 Reproduce normal rhythm, CPR

Scenario 6 (S6): 1. Reproduce ventricular fibrillation

continuosly, CPR

Scenario 7 (S7): 1. Apply first shock, CPR

2. Apply second shock, CPR3. Reproduce normal rhythm, CPR

4. Apply third shock, CPR

5. Reproduce normal rhythm, CPR


Scenario 8 (S8): 1. Apply first shock, CPR

2. Apply second shock, CPR3. Apply third shock, CPR

4. Reproduce normal rhythm, CPR

ME PAD Series Dimension


Тор



Rear



Packaging



Approx. 5.6kg

ME PAD Automatic ME PAD Trainer

Layman defibrillation to help sudden cardiac arrest

Accessory Information



Bag

Standard accessory



Battery

Standard accessory



Pads

Standard accessory



Pediatric Pads

Optional accessory



Wall Cabinet

Optional accessory



Wall Holder

Optional accessory



Remote Control

for ME PAD Trainer Standard accessory



Training Pads

for ME PAD Trainer
Optional accessory